

Quality Products for Quality Water

## NRO- 1L Reverse Osmosis Systems



### Operating Parameters

- Operating Pressure: 150-200 psig
- Nominal Recovery: 75%
- Nominal Salt Rejection: 98-99%
- Operating Temperature: 45-85° F
- Design Temperature: 50° F
- Minimum Inlet Pressure: 30 psig
- Control Circuit: 120 VAC, 1-phase, 60 Hz.

### Materials of Construction

- Skid Frame: Powder-coated carbon steel
- Membrane Housings: FRP (300 psig rated)
- Prefilter Housing: Polypropylene
- Low pressure piping: Sch 80 PVC
- High pressure piping: Sch 10 304SS

### Pump and Motor

- Pump: 304/316SS vertical multi-stage centrifugal
- Motor: TEFC, 460 VAC, 3-phase, 60 Hz.

### Standard Features

- 8" x 40" Low-Energy membrane elements (TFC)
- 5-micron sediment pre-filter housing
- Automatic inlet shut-off valve
- Solid-state digital controller (NEMA-4X)
- Product water conductivity monitor
- Operating pressure gauges
- Product, concentrate, and recycle flow meters
- Concentrate and recycle flow control valves
- Low inlet pressure switch with shutdown alarm

### Optional Equipment Available

- PLC / BMS communication option
- Water softeners and carbon filter pretreatment
- Pretreatment chemical injection systems
- Atmospheric storage tanks with level control and repressurization pump
- Membrane clean-in-place (CIP) systems

### Overview

The NECO NRO-1L Reverse Osmosis System is a specialized, hybrid design that combines the simple operation and economical features of a traditional 4" style machine with higher product flow rates and industrial appearance of an 8" style machine. The use of single membrane element housings significantly reduce the skid footprint making it perfect for locations with tight available floor-space.

MODEL NUMBER	CAPACITY		ELEMENT QUANTITY	VESSEL QUANTITY	RO FEED	RO REJECT	SYSTEM PIPING CONNECTIONS (INCHES)			PUMP HP	OVERALL DIMENSIONS (INCHES)			SHIPPING WEIGHT
	GPM	GPD			GPM	GPM	INLET FEED	PERMEATE	RO REJECT		A LENGTH	B WIDTH	C HEIGHT	LBS.
NRO-22K-8H-1L	15	21,600	3	3	20	5	1 1/2	1	3/4	7.5	72	38	75	2,200
NRO-29K-8H-1L	20	28,800	4	4	27	7	1 1/2	1 1/2	1	10	72	38	75	2,300
NRO-36K-8H-1L	25	36,000	5	5	33	8	1 1/2	1 1/2	1	10	72	38	75	2,400
NRO-43K-8H-1L	30	43,200	6	6	40	10	1 1/2	1 1/2	1	15	72	38	81	2,500



888-569-2837



info@nancrede.com



calculate needs

request a quote